

INDUSTRIAL COMPONENT DATA

MSTB 2,5 HC/12-STF-5,08BD:1-12 1143358 PHOENIX CONTACT Connector for printed circuit board, number of poles:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5 HC/12-STF-5,08BD:1-12



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5 HC/12-STF-5,08BD:1-12
Catalog number	1143358
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-7A40C38D16
Generated	2026-08-06

Product Overview

Connector for printed circuit board, number of poles: 12, pitch: 5,08 mm, color: green

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 16 A (see derating curve), sizing voltage (III/2): 320 V, surface contacts: Tin, contact type: Connection female, Number of rows: 1, Number of poles per row: 12, article family: MSTB 2.5 HC/..-STF, pitch: 5.08 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, Stecksystem: POWER COMBICON 2.5, Lock: Locking by screw, type of packaging: boxed packaging

PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 16 A (see derating curve), rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of rows: 1, number of positions: 12, product range: MSTB 2,5 HC/..-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5 HC, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family MSTB 2,5 HC/..-STF

Product line COMBICON Connectors M

Number of positions 12
Pitch 5.08 mm
Number of rows 1
Data management status
Article revision 02
Electrical properties Nominal current IN 16 A (see derating curve)
Nominal voltage UN 320 V
Contact resistance 0.6 mΩ
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection data Connection technology
Type Standard
Connector system COMBICON MSTB 2,5 HC
Nominal cross section 2.5 mm²
Contact connection type Socket
Interlock
Locking type Screw locking mechanism
Mounting flange Screw flange
Tightening torque 0.3 Nm
Conductor connection
Connection method Screw connection with tension sleeve
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²
2 conductors with the same cross section, flexible, with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5 HC/12-STF-5,08BD:1-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.