

INDUSTRIAL COMPONENT DATA

MSTBA 2,5 HC/ 4-G-5,08 BK 1711392 PHOENIX CONTACT

Housing base printed circuit board, number of poles: 4, pi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBA 2,5 HC/ 4-G-5,08 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBA 2,5 HC/ 4-G-5,08 BK
Catalog number	1711392
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-DAE3CD9E48
Generated	2026-08-05

Product Overview

Housing base printed circuit board, number of poles: 4, pitch: 5,08 mm, color: black, surface of contact: Tin, assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 16 A (see derating curve), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MSTBA 2.5 HC/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5 HC, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Housing base printed circuit board, nominal current: 16 A, voltage and sizing (III/2): 320 V, number of poles: 4, pitch: 5,08 mm, color: black, surface of contact: Tin, assembly: wave Soldering

Data commercial

Key order One million seven hundred eleven thousand three hundred ninety two

Packing unit 50 pcs

Key selling AABAAA -

Minimum order quantity 50 pcs

EAN Four trillion fifty five billion six hundred twenty six million five hundred seventeen thousand three hundred forty six

Unit weight (excluding packaging) 1,484 g

Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred thirty

Dimensions

Length [l] 12 mm

Width 22,32 mm

Step 5,08 mm

Average Of 15.24 mm

Width [w] 22,32 mm

Height [h] 12,1 mm

Height of construction 8.6 mm

Length of the pin welding 3.5 mm

Dimensions of pin 1 x 1 mm

Separation between rods 5.00 mm

Length 12 mm

Overview

Family of articles MSTBA 2,5 HC/..-G -

Color black

Number of poles Four

Environmental Product Compliance

China RoHS Space of time for the intended use: unlimited = FEUP-e

No dangerous substances above the thresholds

Ratings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred two

eCl@ss 9.0 Twenty seven million four hundred forty thousand four hundred two

ETIM

ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBA 2,5 HC/ 4-G-5,08 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.