

INDUSTRIAL COMPONENT DATA

MSTBC 2,5/ 3-ST-5,08 GNTQ CP3 1710501 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBC 2,5/ 3-ST-5,08 GNTQ CP3



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBC 2,5/ 3-ST-5,08 GNTQ CP3
Catalog number	1710501
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-07CA202824
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: turquoise green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact type: Female connection, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MSTBC 2.5/.. -ST, pitch: 5.08 mm, connection type: Crimped connection, conductor/printed circuit board connection direction: 0 °, Clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: packed in box, Corresponding crimped female contacts, with indications regarding the current [A] and the range of conductor cross-sections [mm²]: 10A/MSTBC-MT 0.5-1.0 (3190564); 10A/MSTBC-MT 0.5-1.0 BA (3190645); 12A/MSTBC-MT 1.5-2.5 (3190551); 12A/MSTBC-MT 1.5-2.5 BA (3190658). BA = Contacts on Ribbon

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1710501

Packing unit 1

GTIN 4055626157337

Custom tariff number 85472000

Item properties

Brief article description Printed-circuit board connector

Plug-in system CLASSIC COMBICON

Type of contact Female connector

Range of articles MSTBC 2,5/...-ST

Pitch 5.08 mm

Number of positions 3

Connection method Crimp connection

Number of levels 1

Number of connections 3

Number of potentials 3

Electrical parameters

Rated current 12 A

Rated insulation voltage (III/2) 320 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section flexible 0.5 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 20 ... 14

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Metal surface terminal point (top layer) Tin (Sn)

Metal surface contact area (top layer) Tin (Sn)

Material data - housing

Insulating material PA

Insulating material group I

CTI according to IEC 60112 600

Flammability rating according to UL 94 V0

Glow wire flammability index GWFI according to EN 60695-2-12 850

Glow wire ignition temperature GWIT according to EN 60695-2-13 775

Temperature for the ball pressure test according to EN 60695-10-2 125 °C

Dimensions for the product

Dimensional drawing

Length [l] 25 mm

Width [w] 15.2 mm

Height [h] 10 mm

Pitch 5.08 mm

Height (without solder pin) 10 mm

Dimension a 10.16 mm

Packaging information

Type of packaging packed in cardboard

Pieces per package 50

Denomination....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBC 2,5/ 3-ST-5,08 GNTQ CP3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.