

INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 2-G1R KMGY AU 1077604 PHOENIX CONTACT PCB headers, number of positions: 2, pitch: 5 mm, color: li..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 2-G1R KMGY AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 2-G1R KMGY AU
Catalog number	1077604
Category	Printed circuit board connector
Minimum order	1000 Pcs
Document ID	EO-204F6E9CA0
Generated	2026-08-05

Product Overview

PCB headers, number of positions: 2, pitch: 5 mm, color: light gray, contact surface: Gold, pin layout: Linear pinning, Article with lateral pin exit

Printed circuit board base case, color: bright gray, contact surface: Gold, contact type: Male, number of rows: 1, number of poles: 2, family of items: MSTBO 2.5/.. -G1R Au, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Orthogonal, locking: without, packaging type: boxed, Item with side pin output on the right

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1077604

Packing unit 1

GTIN 4055626790381

Custom tariff number 85366930

Item properties

Packaging information

Classifications

Dimensions for the product

Standards and Regulations

Item properties[Number of positions 2](#)[Pin layout Linear pinning](#)[Back to top](#)[Dimensions for the product](#)[Pitch 5 mm](#)[Back to top](#)[Packaging information](#)[Pieces per package 50](#)[Denomination packing units Pcs.](#)[Back to top](#)[Standards and Regulations](#)[Flammability rating according to UL 94 V0](#)[Back to top](#)[Classifications](#)[eCl@ss](#)[eCl@ss 4.0 272607xx](#)[eCl@ss 4.1 27260701](#)[eCl@ss 5.0 27260701](#)[eCl@ss 5.1 27260700](#)[eCl@ss 6.0 27260700](#)[eCl@ss 7.0 27440402](#)[eCl@ss 8.0 27440402](#)[eCl@ss 9.0 27440402](#)[Back to top](#)[ETIM](#)[ETIM 3.0 EC001121](#)[ETIM 4.0 EC002637](#)[ETIM 5.0 EC002637](#)[ETIM 6.0 EC002637](#)[ETIM 7.0 EC002637](#)[Back to top](#)[UNSPSC](#)[UNSPSC 6.01 30211801](#)[UNSPSC 7.0901 39121432](#)[UNSPSC 11 34131203](#)[UNSPSC 12.01 39121432](#)[UNSPSC 13.2 39121409](#)[UNSPSC 18.0 39121409](#)[UNSPSC 19.0 39121409](#)[UNSPSC 20.0 39121409](#)[UNSPSC 21.0 39121409](#)[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 2-G1R KMGY AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.