

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/0,6-150/M12FS P+F 1575013 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/0,6-150/M12FS P+F



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/0,6-150/M12FS P+F
Catalog number	1575013
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-6533D9A959
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, halogen-free PUR, irradiation cross-linked, orange RAL 2003, M12 straight male connector, encoding: A, a M12 straight connection female, coding: A, cable length: 0.6 m

Sensor/actuator cable, 5-position, PUR halogen-free, irradiated, orange RAL 2003, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 0.6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

No. of cable outlets 1

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 5
Coding type A
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A
Cable/lineCable length 0.6 m
PUR irradiated halogen-free orange [151]
Number of positions 5
Shielded no
Cable type PUR irradiated halogen-free orange [151]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 0.34 mm²
Wire diameter incl. insulation 1.05 mm $\pm 0.05 \text{ mm}$
External cable diameter 5.90 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color orange RAL 2003
Conductor material Bare Cu litz wires
Material wire insulation PE
Single wire, color brown, white, blue, black, green-yellow
Overall twist 5 cores, twisted
Max. conductor resistance $\leq 57 \text{ }\Omega/\text{km}$
Nominal voltage, cable 25...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/0,6-150/M12FS P+F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.