

INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 4-G1L KMGY AU 1077607 PHOENIX CONTACT PCB headers, number of positions: 4, pitch: 5 mm, color: li..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 4-G1L KMGY AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 4-G1L KMGY AU
Catalog number	1077607
Category	Printed circuit board connector
Minimum order	1000 Pcs
Document ID	EO-D4A5D90D01
Generated	2026-08-06

Product Overview

PCB headers, number of positions: 4, pitch: 5 mm, color: light gray, contact surface: Gold, pin layout: Linear pinning
Printed circuit board base case, color: bright gray, contact surface: Gold, contact type: Male, number of rows: 1, number of poles: 4, family of items: MSTBO 2.5/.. -G1L Au, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Orthogonal, locking: without, packaging type: boxed, Item with side pin output on the left
PCB headers, color: light gray, contact surface: Au, contact connection type: Pin, number of rows: 1, number of positions: 4, product range: MSTBO 2,5/..-G1L Au, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, Pin connector pattern alignment: Orthogonal, locking: without, type of packaging: packed in cardboard, Product with pin output on left side

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers
Product family MSTBO 2,5/..-G1L Au
Type Header perpendicular to the PCB
Number of positions 4
Pitch 5 mm
Number of rows 1
Pin layout Linear pinning

Solder pins per potential 1
Data management status
Article revision 01
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - housing
Color (Housing) light gray (7035)
DimensionsPitch 5 mm
Width [w] 19.95 mm
Height [h] 16.5 mm
Length [l] 14.65 mm
Solder pin length [P] 3.5 mm
Pin dimensions 1 x 1 mm
PCB design
Hole diameter 1.4 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 105 °C (dependent on the derating curve)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Relative humidity (storage/transport) 30 % ... 70 %
Ambient temperature (assembly) -5 °C ... 100 °C
Packaging specificationsType of packaging packed in cardboard
Outer packaging type Carton
ETIM for 1077607 Connectors (EC002637)
Feature Name
Feature Value
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 4-G1L KMGY AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.