

INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 4-G1R BUGY CD:2,3,4 1016977 PHOENIX

CONTACT PCB headers, number of positions: 4, pitch: 5 mm, pin..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 4-G1R BUGY CD:2,3,4



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 4-G1R BUGY CD:2,3,4
Catalog number	1016977
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-22B256C493
Generated	2026-08-06

Product Overview

MSTBO 2,5/ 4-G1R BUGY CD:2,3,4 1016977 PHOENIX CONTACT PCB headers, number of positions: 4, pitch: 5 mm, pin..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Pin
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	5 mm
Modular spacing connections (EF006827)	5 mm
Rated current In (EF008250)	12 A
Rated voltage (EF000228)	320 V
Rated surge voltage (EF002993)	4 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	1.4 mm
Length pin (EF006825)	3.5 mm
Material insulation body (EF007543)	Other

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	Other
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of banding (EF007011)	Carton (for SMD)

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

PCB headers, number of positions: 4, pitch: 5 mm, pin layout: Linear pinning
Printed circuit board base housing, nominal section: 2.5 mm², color: bluish gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 4, family of articles: MSTBO 2.5/.. -G1R, pitch: 5 mm, connection type: plug-in, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, lock: without, packaging type: boxed packed, Fixed pole coding: 2, 3, 4, item with side pin output on the right

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 4-G1R BUGY CD:2,3,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.