

INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 6-GL-5,08 BK 1982376 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 6-GL-5,08 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 6-GL-5,08 BK
Catalog number	1982376
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-1ACF2352B5
Generated	2026-08-05

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: MSTBO 2.5/.. -GL, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1982376

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918954994

Weight per Piece (excluding packing) 5.410 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [L] 49.14 mm

Width 8.6 mm

Pitch 5.08 mm

Dimension a 25.4 mm

Width [w] 8.6 mm

Height [h] 30.48 mm

Height 30.48 mm

Length of the solder pin 3.2 mm

Pin dimensions 1.2 x 0.32 mm

Length 49.14 mm

General

Range of articles MSTBO 2,5/...-GL

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color black

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 6-GL-5,08 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.