

INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 8-GL-5,08 CW CD 2,7 1973181 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 8-GL-5,08 CW CD 2,7



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 8-GL-5,08 CW CD 2,7
Catalog number	1973181
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-A2C39C4E19
Generated	2026-08-04

Product Overview

Feed-through header

Printed circuit board base case, nominal section: 2.5 mm², color: cream white, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: MSTBO 2.5/.. -GL, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.2 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

PCB base socket, nominal cross-section: 2.5 mm², colour: creamy white, rated current: 8 A, dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: plug, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, product series: MSTBO 2.5/.. -GL, pitch: 5.08 mm, mounting: Wave soldering, pin layout: Linear pinning, pin length [P]: 3.2 mm, number of solder pins per potential: 1, plug system: COMBICON MSTB 2.5, Insertion pin orientation: Orthogonal, locking: none, fastening type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1973181

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918942175

Weight per Piece (excluding packing) 8.640 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 59.3 mm

Width 8.6 mm

Pitch 5.08 mm

Dimension a 35.56 mm

Width [w] 8.6 mm

Height [h] 40.64 mm

Height 40.64 mm

Length of the solder pin 3.2 mm

Pin dimensions 1.2 x 0.32 mm

Length 59.3 mm

General

Range of articles MSTBO 2,5/..-GL

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color cream

Number of positions 8

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1973181 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

8

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Rated current I_n (EF008250)

8 A

R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 8-GL-5,08 CW CD 2,7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.