

## INDUSTRIAL COMPONENT DATA

# MSTBP 2,5/21-ST 1765962 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBP 2,5/21-ST



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | MSTBP 2,5/21-ST |
| Catalog number  | 1765962         |
| Category        | Cable connector |
| Minimum order   | 50 Pcs          |
| Document ID     | EO-46D552FBBF   |
| Generated       | 2026-08-04      |

## Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 21, number of rows: 1, number of poles: 21, number of connections: 21, family of articles: MSTBP 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1765962

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 127 (CC-2005)

GTIN 4017918031992

Weight per Piece (excluding packing) 43.700 g

Custom tariff number 85366990

Country of origin PL (Poland)

**Dimensions**

Length [ l ] 21.3 mm

Width [ w ] 105 mm

Height [ h ] 15 mm

Pitch 5 mm

Dimension a 100 mm

**General**

Range of articles MSTBP 2,5/..-ST

Number of positions 21

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 12 ANominal cross section 2.5 mm<sup>2</sup>Maximum load current 12 A (with a 2.5 mm<sup>2</sup> conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

**Connection data**Conductor cross section solid min. 0.2 mm<sup>2</sup>Conductor cross section solid max. 2.5 mm<sup>2</sup>Conductor cross section flexible min. 0.2 mm<sup>2</sup>Conductor cross section flexible max. 2.5 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section fle...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBP 2,5/21-ST with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.