

INDUSTRIAL COMPONENT DATA

SAC-3P-10,0-500/M 8FR VA 0,34 1562806 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-10,0-500/M 8FR VA 0,34



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-10,0-500/M 8FR VA 0,34
Catalog number	1562806
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-80A6D12DFB
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 3-pole, PVC, grey RAL 7001, free cable end, to M8 angled connection female, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1562806

Packing unit 5 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356299312

Weight per Piece (excluding packing) 350.200 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 10 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67
IP68
IP69K
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PVC gray
Cable type (abbreviation) PVC
Cable abbreviation LiYY
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section $3 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $19 \times 0.15 \text{ mm}$
Core diameter including insulation $1.26 \text{ mm} \pm 0.05 \text{ mm}$
Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color gray
Outer sheath thickness $\geq 0.76 \text{ mm}$
External cable diameter $D 4.3 \text{ mm} \pm 0.2 \text{ mm}$
Minimum bending radius, fixed installation $5 \times D$
Minimum bending radius, flexible install...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-10,0-500/M 8FR VA 0,34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.