

INDUSTRIAL COMPONENT DATA

MSTBT 2,5/ 4-ST BD:62-A1SO 1442150 PHOENIX CONTACT

Connector for printed circuit board, nominal section: 2.5..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBT 2,5/ 4-ST BD:62-A1SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBT 2,5/ 4-ST BD:62-A1SO
Catalog number	1442150
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-956C5C8F8A
Generated	2026-08-02

Product Overview

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Female, number of rows: 1, number of poles: 4, family of articles: MSTBT 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed
Printed circuit board connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1442150 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5 mm
Modular spacing connections (EF006827)
5 mm
Angle contact/conductor connection (EF007546)
Other
Rated current I_n (EF008250)
12 A
Rated voltage (EF000228)
320 V
Rated surge voltage (EF002993)
4 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)
0.2 mm²
Connectable conductor cross section fine-strand with cable end sleeve (EF007339)
0.25 mm²
Connectable conductor cross section solid-core (EF007337)
0.2 mm²
Type of electric connection (EF003961)
Screw connection
Connectable cable type (EF006816)
Tubular cable
Material of contact surface (EF004020)
Tin
Material contact (EF007544)
Copper
Material insulation body (EF007543)
Polyamide (PA)
Housing material (EF001596)
Other
Housing colour (EF000136)
Green
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBT 2,5/ 4-ST BD:62-A1SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.