

INDUSTRIAL COMPONENT DATA

MSTBT 2,5/ 4-ST GY7035 CP1,2,4 1767995 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBT 2,5/ 4-ST GY7035 CP1,2,4



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBT 2,5/ 4-ST GY7035 CP1,2,4
Catalog number	1767995
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-17972D3D11
Generated	2026-08-05

Product Overview

Cable connector

Connector for printed circuit board, nominal section: 2.5 mm², color: luminous gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MSTBT 2,5/..-ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, pin arrangement: Linear pin arrangement, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2,5, locking: without, fixing type: without, packaging type: Boxed Packaging

PCB connector, nominal cross section: 2.5 mm², color: light gray, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: MSTBT 2,5/..-ST, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, pin layout: Linear pinning, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family MSTBT 2,5/..-ST

Product line COMBICON Connectors M

Number of positions 4

Pitch 5 mm
Number of connections 4
Number of rows 1
Number of potentials 4
Mounting flange without
Pin layout Linear pinning
Data management status
Article revision 04
Electrical propertiesNominal current I_N 12 A
Nominal voltage U_N 320 V
Contact resistance 1.2 m Ω
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MSTB 2,5
Nominal cross section 2.5 mm²
Contact connection type Socket
Interlock
Locking type without
Mounting flange without
Conductor connection
Connection method Screw connection with tension sleeve
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²
2 conductors with the same cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBT 2,5/ 4-ST GY7035 CP1,2,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.