

INDUSTRIAL COMPONENT DATA

MSTBT 2,5/ 4-ST BKBDWH:-+OUT 1710782 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBT 2,5/ 4-ST BKBDWH:-+OUT



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBT 2,5/ 4-ST BKBDWH:-+OUT
Catalog number	1710782
Category	Cable connector
Minimum order	500 Pcs
Document ID	EO-884D76A167
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: MSTBT 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, pin arrangement: Linear pin arrangement, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1710782

Packing unit 1

GTIN 4055626196015

Custom tariff number 85366990

Dimensions

Width [w] 20 mm

Pitch 5 mm

Dimension a 15 mm

General

Range of articles MSTBT 2,5/..-ST

Number of positions 4

Connection method Screw connection

Insulating material group I

Rated voltage (III/2) 320 V

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Flammability rating according to UL 94 V0

Screw thread M3

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

UNSPSC 13.239121409

ETIM for 1710782 Connectors (EC002638)

Feature Name**Feature Value**

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5 mm

Modular spacing connections (EF006827)

5 mm

Angle contact/conductor connection (EF007546)

Other

Rated current In (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable en...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBT 2,5/ 4-ST BKBDWH:-+OUT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.