

INDUSTRIAL COMPONENT DATA

Q SET-PG9-0,75/3-ESA BK HUBA 1641824 PHOENIX CONTACT Connector set

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q SET-PG9-0,75/3-ESA BK HUBA



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q SET-PG9-0,75/3-ESA BK HUBA
Catalog number	1641824
Category	Sensor-actuator connector chassis
Minimum order	100 Pcs
Document ID	EO-B5ED2EE499
Generated	2026-08-05

Product Overview

Connector set

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > QUICKON Installation System (QPD)**

Additional Product Information

Key Commercial Data

Orderkey 1641824

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4017918890438

Weight per Piece (excluding packing) 6.000 g

Custom tariff number 39269097

Country of origin PL (Poland)

General

Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.

Color black

Connection method QUICKON connection

Number of positions 3

Wrench size, union nut 19 mm

Tightening torque, union nut 2.5 Nm

Wrench size, contact carrier 19 mm

Tightening torque contact carrier 3.75 Nm

Tightening torque, counter nut 3.75 Nm

Number of connections 3

Cabel

Wire insulation material PVC / PE

Wire diameter including insulation ≥ 2.5 mm

External cable diameter 6 mm ... 12 mm

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -25 °C ... 80 °C (Specifications of the cable manufacturer must be observed.)

-25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.)

Temperature when conductor connected -5 °C ... 50 °C (specifications of the cable manufacturer must also be observed)

Mechanical characteristics

QUICKON connectability max. 10 (if the conductor is connected more than once, seal and cap may need to be replaced.)

Impact category 3

Category of shock impact IK07

Material data

Contact carrier material PA

Insulating material PA

Flammability rating according to UL 94 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q SET-PG9-0,75/3-ESA BK HUBA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.