


INDUSTRIAL COMPONENT DATA

MSTBV 2,5/19-G BK 1755419 PHOENIX CONTACT Housing base for printed circuit board, nominal current: 12 A, num..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBV 2,5/19-G BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBV 2,5/19-G BK
Catalog number	1755419
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-584B2FC484
Generated	2026-08-04

Product Overview

Housing base for printed circuit board, nominal current: 12 A, number of poles: 19, pitch: 5 mm, color: black, surface of contact: Tin, assembly: wave Soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, Number of potentials: 19, Number of rows: 1, Number of poles per row: 19, number of connections: 19, family of articles: MSTBV 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, Stecksystem: CLASSIC COMBICON, Locking: without, packaging type: boxed

PCB socket, nominal cross-section: 2.5 mm², colour: black, rated current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: plug, number of potentials: 19, number of rows: 1, number of poles: 19, number of connections: 19, product series: MSTBV 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug system: COMBICON MSTB 2.5, Insertion pin orientation: Standard, locking: none, fixing type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataArticle featuresProduct Type Basic socket for printed circuit boards

Product Family MSTBV 2.5/.. -G

Product Line COMBICON Connectors M

Number of poles 19

Step 5 mm

Number of connections 19

Number of rows 1

Number of potentials 19

Fixing flange absent

Pin Layout Linear Pinning

Number of Welding Pins per Potential 1

Data maintenance status

Article review 01

Electrical characteristics Rated Current IN 12 A

Rated voltage UN 320 V

Mass Resistivity 2.1 m?

Sizing voltage (III/3) 250 V

Sizing impulse voltage (III/3) 4 kV

Sizing voltage (III/2) 320 V

Sizing Impulse Voltage (III/2) 4 kV

Sizing voltage (II/2) 400 V

Sizing Impulse Voltage (II/2) 4 kV

Montage Mounting type Wave Soldering

Pin Layout Linear Pinning

Material information Material information - contacts

note Complies with WEEE/RoHS, no thread-like materials according to IEC 60068-2-82/JEDEC JESD 201

Contact Material Cu Alloy

Surface Finish Galvanic tin plating

Metal surface contact zone (surface layer) Tin (3 - 5 um Sn)

Metal surface contact area (middle layer) Nickel (1.3 - 3 um Ni)

Metal Surface Welding Area (Surface Layer) Tin (3 - 5 um Sn)

Metal Surface Weld Area (Middle Layer) Nickel (1.3 - 3 um Ni)

Material information - case

Color (Case) Black (9005)

Insulation material PBT

Insulation Material Group IIIa

CTI according to IEC 60112 225

Combustibility class according to UL 94 V0

Notes Note for Operation According to DIN EN 61984, COMBICON connectors are connectors without switchable power (COC). For use in acco...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBV 2,5/19-G BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.