

INDUSTRIAL COMPONENT DATA

PC 5/ 3-GU-7,62 BK 1705063 PHOENIX CONTACT Base housing, number of poles: 3, pitch: 7.62 mm, color: black, c..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/ 3-GU-7,62 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 5/ 3-GU-7,62 BK
Catalog number	1705063
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-0E0157D23B
Generated	2026-08-04

Product Overview

PC 5/ 3-GU-7,62 BK 1705063 PHOENIX CONTACT Base housing, number of poles: 3, pitch: 7.62 mm, color: black, c..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	Fixed connector
Contact type (EF001587)	Pin
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	7.62 mm
Modular spacing connections (EF006827)	7.62 mm
Rated current In (EF008250)	41 A
Rated voltage (EF000228)	630 V
Rated surge voltage (EF002993)	6 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Material of contact surface (EF004020)	Tin
Type of electric connection (EF003961)	Other
Diameter connection pin (EF006823)	1.3 mm
Length pin (EF006825)	4.2 mm
Material insulation body (EF007543)	Other

CONTINUED**Technical Specifications**

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	Black
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C
Type of fastening (EF002442)	Other
Type of banding (EF007011)	Carton (for SMD)

Classification & Catalog Path

eCl@ss 7.1	21043711
eCl@ss 8.0	21043711
eCl@ss 9.0	21043711
ETIM 5.0	EC002246
ETIM 6.0	EC002246
ETIM 7.0	EC002246
Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Base housing, number of poles: 3, pitch: 7.62 mm, color: black, contact surface: Tin, mounting: Wave soldering
Printed circuit board base case, nominal section: 6 mm², color: black, nominal current: 41 A, nominal voltage (III/2): 630 V,
contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 3, family of articles: PC 5/.. -GU, pitch: 7.62
mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4.2 mm, number of solder pins per
potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: inverted, locking: without, fixing type: without,
packaging type: boxed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/ 3-GU-7,62 BK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.