


INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/11-G BK 1760048 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/11-G BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/11-G BK
Catalog number	1760048
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-29DA131093
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, family of articles: MSTBVA 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed
PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 11, pitch: 5 mm, color: black, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1760048

Packing unit 1 pc

Minimum order quantity 50 pc

GTIN 4046356330831

Weight per Piece (excluding packing) 4.990 g

Custom tariff number 85366930

Country of origin DE (Germany)

[Drawings](#)

[General](#)

[Environmental Product Compliance](#)

[Dimensions](#)

[Standards and Regulations](#)

[Classifications](#)

[Drawings](#)

[Diagram](#)

Type: MSTB 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: SMSTB 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: FKCT 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: MSTBT 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: MSTBP 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: FKCN 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: FKCV(W/R) 2,5/...-ST with MSTBVA 2,5/...-G

[Back to top](#)[Dimensions](#)

Length [l] 8.57 mm

Width 57 mm

Pitch 5 mm

Dimension a 50 mm

Width [w] 57 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 8.57 mm

[Back to top](#)[General](#)

Range of articles MSTBVA 2,5/...-G

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Color black

Number of positions 11

[Back to top](#)[Standards and Regulations](#)

Connection in acc. with standard EN-VDE

CSA

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 4.0 27260700
eCl@ss 4.1 27260700
eCl@ss 5.0 27260700
eCl@ss 5.1 27260700
eCl@ss 6.0 27260700
eCl@ss 7.0 27440402
eCl@ss 8.0 27440402
eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/11-G BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.