

INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/20-G BK 1723706 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/20-G BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/20-G BK
Catalog number	1723706
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-F65BF50F4C
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, Number of potentials: 20, Number of rows: 1, Number of poles per row: 20, number of connections: 20, family of articles: MSTBVA 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, Stecksystem: CLASSIC COMBICON, Locking: without, packaging type: boxed

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 20, pitch: 5 mm, color: black, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1723706

Packing unit 1 pc

Minimum order quantity 50 pc

GTIN 4046356122870

Weight per Piece (excluding packing) 8.800 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Standards and Regulations

Classifications

General

Environmental Product Compliance

Dimensions

Length [l] 8.57 mm

Width 102 mm

Pitch 5 mm

Dimension a 95 mm

Width [w] 102 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Length 8.57 mm

[Back to top](#)General

Range of articles MSTBVA 2,5/...-G

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Color black

Number of positions 20

[Back to top](#)Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

[Back to top](#)Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27260700

eCl@ss 4.1 27260700

eCl@ss 5.0 27260700

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

[Back to top](#)ETIM

ETIM 3.0 EC001121

ETIM 4.0 EC002637

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

[Back to top](#)UNSPSC

UNSPSC 6.01 30211810

UNSPSC 7.0901 39121409

UNSPSC 11 39121409
UNSPSC 12.01 39121409
UNSPSC 13.2 39121409
UNSPSC 18.0 39121409
UNSPSC 19.0 39121409
UNSPSC 20.0 39121409
UNSPSC 21.0 39121409

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/20-G BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.