

## INDUSTRIAL COMPONENT DATA

# MSTBVA 2,5/ 3-G PA1,3 1230875 PHOENIX CONTACT Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 3-G PA1,3



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | MSTBVA 2,5/ 3-G PA1,3           |
| Catalog number  | 1230875                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1000 Pcs                        |
| Document ID     | EO-DDF61FBA41                   |
| Generated       | 2026-08-05                      |

## Product Overview

Printed circuit board base housing, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Male, number of potentials: 2, number of rows: 1, number of poles: 3, number of connections: 2, article family: MSTBVA 2.5/.. -G, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, clamping type: without, packaging type: boxed

Base housing printed circuit board, nominal section: 2.5 mm<sup>2</sup>, color: green, rated current: 12 A, sizing voltage (III/2): 320 V, surface contacts: Tin, contact type: Male, Number of rows: 1, Number of poles per row: 3, article family: MSTBVA 2.5/.. -G, pitch: 5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, plug-in system: CLASSIC COMBICON, Plug-in face orientation: Standard, Locking: sin, fixing type: sin, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

ETIM for 1230875 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5 mm

Modular spacing connections (EF006827)

5 mm

Rated current  $I_n$  (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contact surface (EF004020)

Tin

Type of electric connection (EF003961)

Other

Diameter connection pin (EF006823)

1.4 mm

Length pin (EF006825)

3.9 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of fastening (EF002442)

Other

Type of banding (EF007011)

Carton (for SMD)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 3-G PA1,3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.