

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MR/ 0,2-PUR/M12FR SH 1401325 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MR/ 0,2-PUR/M12FR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MR/ 0,2-PUR/M12FR SH
Catalog number	1401325
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-6E70F82CD2
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded, Angled male connector M12, coding: A, a Angled connection female M12, coding: A, cable length: 0.2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1401325

Packing unit 1

GTIN 4046356549479

Custom tariff number 85444290

Dimensions

Length of cable 0.2 m

General

Rated voltage 48 V AC

60 V DC

Number of positions 5

Coding A - standard

Insertion/withdrawal cycles >= 100

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation LiF9YC11Y

UL AWM style 20549

Conductor cross section 5x 0.34 mm² (Signal line)

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)

Wire colors Brown, white, blue, black, gray

Overall twist 5 wires around filler to the core

Shielding Tinned copper braided shield

Optical shield covering 80 %

External sheath, color black RAL 9005

External cable diameter D 5.25 mm ±0.2 mm

Smallest bending radius, fixed installation 26 mm

Smallest bending radius, movable installation 52 mm (up to +60°C)

Number of bending cycles 10000000

Bending radius 52 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance 70 G?·km (at 20 °C)

Conductor resistance max. 57 ?/km (at 20 °C)

Nominal voltage, cable 300 V (at 20 °C)

Test voltage Core/Core 3000 V (at 20 °C)

Special properties Flexible cable conduit capable

Flame resistance in accordance with UL 758/1581 FT2

DIN EN 60332-2-2 (20 s)

Halogen-free in accordance with DIN VDE 0472 part 815

Resistance to oil in accordance w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MR/ 0,2-PUR/M12FR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.