


INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 6-G-5,08 BD3:1-6 1005172 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 6-G-5,08 BD3:1-6



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 6-G-5,08 BD3:1-6
Catalog number	1005172
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-43B66B1E43
Generated	2026-08-04

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, article family: MSTBVA 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, clamping type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1005172

Packing unit 1

GTIN 4055626474854

Custom tariff number 85366930

Dimensions

Length [l] 8.6 mm

Width 32.48 mm

Pitch 5.08 mm

Width [w] 32.48 mm

Height [h] 15.9 mm

Height 12 mm

Length of the solder pin 3.9 mm

Pin dimensions 1 x 1 mm

Length 8.6 mm

General

Range of articles MSTBVA 2,5/...-G

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Color green

Number of positions 6

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 5.0EC002637ETIM 6.0EC002637

ETIM for 1005172 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

6

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Rated current I_n (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 6-G-5,08 BD3:1-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.