

INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 6-G 5PA 1714552 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 6-G 5PA



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 6-G 5PA
Catalog number	1714552
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-329F627872
Generated	2026-08-05

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, Number of potentials: 6, Number of rows: 1, Number of poles per row: 6, number of connections: 6, family of articles: MSTBVA 2.5/.. -G, pitch: 5 mm, mounting: Wave welding, Stecksystem: CLASSIC COMBICON, Locking: without, packaging type: boxed

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 6, pitch: 5 mm, color: green, contact surface: Tin, mounting: Wave soldering

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1714552

Packing unit 1

GTIN 4055626366845

Custom tariff number 85366930

Drawings

General

Classifications

Dimensions

[Environmental Product Compliance](#)

[Drawings](#)

[Diagram](#)

Type: MSTB 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: SMSTB 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: FKCT 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: MSTBT 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: MSTBP 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: FKCN 2,5/...-ST with MSTBVA 2,5/...-G

[Diagram](#)

Type: FKCV(W/R) 2,5/...-ST with MSTBVA 2,5/...-G

[Back to top](#)[Dimensions](#)

[Pitch 5 mm](#)

[Pin dimensions 1 x 1 mm](#)

[Back to top](#)[General](#)

[Range of articles MSTBVA 2,5/...-G](#)

[Color green](#)

[Number of positions 6](#)

[Back to top](#)[Environmental Product Compliance](#)

[China RoHS Environmentally friendly use period: unlimited = EFUP-e](#)

[No hazardous substances above threshold values](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 4.0 27260700](#)

[eCl@ss 4.1 27260700](#)

[eCl@ss 5.0 27260700](#)

[eCl@ss 5.1 27260700](#)

[eCl@ss 6.0 27260700](#)

[eCl@ss 7.0 27440402](#)

[eCl@ss 8.0 27440402](#)

[eCl@ss 9.0 27440402](#)

[Back to top](#)[ETIM](#)

[ETIM 5.0 EC002637](#)

[ETIM 6.0 EC002637](#)

[ETIM 7.0 EC002637](#)

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 6-G 5PA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.