


INDUSTRIAL COMPONENT DATA

PT 2,5-PE/3L/2P 3012316 PHOENIX CONTACT Multi-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-PE/3L/2P



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-PE/3L/2P
Catalog number	3012316
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-24E3A726B9
Generated	2026-08-03

Product Overview

Multi-level terminal block

Multi-floor terminal block, nominal voltage: 250 V, nominal current: 10 A, number of connections: 12, connection type: Push-in connection / plug-in connection, 1., 2., 3. and 4th floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3012316

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 290 (C-1-2017)

GTIN 4046356728232

Weight per Piece (excluding packing) 28.970 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 4

Number of connections 12
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 61984
Nominal current I_N 10 A
Maximum load current 10 A (with a 2.5 mm² conductor cross section)
Nominal voltage U_N 250 V
Open side panel Yes
Insertion/withdrawal cycles mechanical 50
Result of surge voltage test Test passed
Surge voltage test setpoint 4.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.21 kV
Result of tight fit on support Test passed
Tight fit on carrier NS 35
Setpoint 1 N
Short circuit stability result Test passed
Conductor cross section short circuit testing 1 mm²
Short-time current 0.12 kA
Result of thermal test Test passed
Proof of thermal characteristics (needle flame) effective duration 30 s
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-PE/3L/2P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.