

INDUSTRIAL COMPONENT DATA

PT 1,5/S-3L 3213713 PHOENIX CONTACT Multi-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-3L



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/S-3L
Catalog number	3213713
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-8E1CE7C8E3
Generated	2026-08-03

Product Overview

Multi-level terminal block

Multi-floor terminal block, nominal voltage: 500 V, nominal current: 15 A, connection type: Push-in connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3213713

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 38 (C-1-2017)

GTIN 4046356572484

Weight per Piece (excluding packing) 11.960 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 6

Nominal cross section 1.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 15 A
Maximum load current 15 A
Nominal voltage U_N 500 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
1.5 mm² / 0.4 kg
Tensile test result Test passed
Conductor cross section tensile test 0.14 mm²
Tra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-3L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.