

INDUSTRIAL COMPONENT DATA

PT 2,5-4L/2P 3012310 PHOENIX CONTACT Multi-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2,5-4L/2P



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2,5-4L/2P
Catalog number	3012310
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-1A5D7E6F5F
Generated	2026-07-29

Product Overview

Multi-level terminal block

Multi-floor terminal block, nominal voltage: 250 V, nominal current: 10 A, number of connections: 12, connection type: Push-in connection / plug-in connection, Sizing cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3012310

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 290 (C-1-2017)

GTIN 4046356645966

Weight per Piece (excluding packing) 24.500 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 4

Number of connections 12

Potentials 4

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)

Ambient temperature (operation) -60 °C ... 100 °C (dependent on the derating curve)

Ambient temperature (assembly) -40 °C ... 100 °C

Maximum load current 10 A (with a 2.5 mm² conductor cross section)

Nominal current I_N 10 A

Nominal voltage U_N 250 V

Open side panel Yes

Insertion/withdrawal cycles mechanical 50

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 2.21 kV

Result of tight fit on support Test passed

Tight fit on carrier NS 35

Setpoint 1 N

Short circuit stability result Test passed

Conductor cross section short circuit testing 1 mm²

Short-time current 0.12 kA

Result of thermal test Test passed

Proof of thermal characteristics (needle flame) effective duration 30 s

Oscillation, broadband noise test result Test passed

Test spe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2,5-4L/2P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.