

**INDUSTRIAL COMPONENT DATA**

# MKKDSN 1,5/ 3 H1L 1891739 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDSN 1,5/ 3 H1L



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKKDSN 1,5/ 3 H1L              |
| Catalog number  | 1891739                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-EA271A8BBF                  |
| Generated       | 2026-08-04                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm<sup>2</sup>, number of rows: 2, number of poles per row: 3, family of articles: MKKDSN 1.5, pitch: 5 mm, type of connection: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, Mounting: Wave soldering, conductor/PCB connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of soldering pins per potential: 1, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 1891739

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918422158

Weight per Piece (excluding packing) 6.060 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [ L ] 18.3 mm

Pitch 5 mm

Dimension a 10 mm

Width [ w ] 17.5 mm

Height 20 mm

Height [ h ] 22.6 mm

Solder pin [P] 3.5 mm

Pin spacing 10 mm

Hole diameter 1.3 mm

#### General

Range of articles MKKDSN 1,5

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current  $I_N$  13.5 A

Nominal cross section 1.5 mm<sup>2</sup>

Solder pin surface

Internal cylindrical gage A1

Stripping length 6 mm

Number of positions 3

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

#### Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.14 mm<sup>2</sup>

2 conductors with same cross section, solid max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.14 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.5 mm<sup>2</sup>

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm<sup>2</sup>

2 conductors w...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDSN 1,5/ 3 H1L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.