


## INDUSTRIAL COMPONENT DATA

# MVSTBR 2,5/ 4-ST-5,08 AU BD:X1 1712396 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5/ 4-ST-5,08 AU BD:X1



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MVSTBR 2,5/ 4-ST-5,08 AU BD:X1 |
| Catalog number  | 1712396                        |
| Category        | Cable connector                |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-DF9F5CC550                  |
| Generated       | 2026-08-06                     |

## Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Gold, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MVSTBR 2.5/..-ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, connection direction conductor/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed PCB connector, nominal cross section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Au, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: MVSTBR 2,5/..-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 90 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

## Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family MVSTBR 2,5/..-ST

Product line COMBICON Connectors M

Number of positions 4

Pitch 5.08 mm

Number of connections 4  
Number of rows 1  
Number of potentials 4  
Data management status  
Article revision 01  
Electrical propertiesNominal current IN 12 A  
Nominal voltage UN 320 V  
Contact resistance 2.5 m?  
Rated voltage (III/3) 250 V  
Rated surge voltage (III/3) 4 kV  
Rated voltage (III/2) 320 V  
Rated surge voltage (III/2) 4 kV  
Rated voltage (II/2) 630 V  
Rated surge voltage (II/2) 4 kV  
Connection dataConnection technology  
Connector system COMBICON MSTB 2,5  
Nominal cross section 2.5 mm<sup>2</sup>  
Contact connection type Socket  
Interlock  
Locking type without  
Mounting flange without  
Conductor connection  
Connection method Screw connection with tension sleeve  
Conductor/PCB connection direction 90 °  
Conductor cross section rigid 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section AWG 24 ... 12  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>  
2 conductors with same cross section, solid 0.2 mm<sup>2</sup> ... 1 mm<sup>2</sup>  
2 conductors with same cross section, flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 1 mm<sup>2</sup>  
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 m...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5/ 4-ST-5,08 AU BD:X1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.