

INDUSTRIAL COMPONENT DATA

MVSTBR 2,5/ 5-ST-5,08 H1L 1098476 PHOENIX CONTACT

Connector for printed circuit board, nominal current: 12 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5/ 5-ST-5,08 H1L



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBR 2,5/ 5-ST-5,08 H1L
Catalog number	1098476
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-85A959C730
Generated	2026-08-03

Product Overview

Connector for printed circuit board, nominal current: 12 A, number of poles: 5, pitch: 5,08 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface contacts: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 5, family of articles: MVSTBR 2.5/..-ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, connection direction driver/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: packed in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

ETIM for 1098476 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Angle contact/conductor connection (EF007546)

Other

Rated current I_n (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Type of electric connection (EF003961)

Screw connection

Connectable cable type (EF006816)

Tubular cable

Material of contact surface (EF004020)

Tin

Material contact (EF007544)

Copper

Material insulation body (EF007543)

Polyamide (PA)

Housing material (EF001596)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5/ 5-ST-5,08 H1L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.