


INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/ 6-ST-3,81 BD14-9SO 1700878 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/ 6-ST-3,81 BD14-9SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/ 6-ST-3,81 BD14-9SO
Catalog number	1700878
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-E9559794A5
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Tin, contact type: Female connection, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: FK-MCP 1.5/.. -ST, pitch: 3.81 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, number of solder pins per potential: 1, plug-in system: MINI COMBICON, Lock: without, fixing type: without, packaging type: boxed

Printed circuit board connector, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, article family: FK-MCP 1.5/.. -ST, pitch: 3.81 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1700878

Packing unit 1

GTIN 4046356503556

Custom tariff number 85366990

Dimensions

Length [l] 21 mm

Width [w] 23.65 mm

Height [h] 12.4 mm

Pitch 3.81 mm

Dimension a 19.05 mm

General

Range of articles FK-MCP 1,5/..-ST

Number of positions 6

Connection method Push-in spring connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 ANominal cross section 1.5 mm²**Connection data**Conductor cross section solid min. 0.14 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.14 mm²Conductor cross section flexible max. 1.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

Minimum AWG according to UL/CUL 28

Maximum AWG according to UL/CUL 16

Specifications for ferrules

Recommended crimping pliers 1212034 CRIMPFOX 6

Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 7 mm ... 9 mmCross section: 0.34 mm²; Length: 7 mm ... 9 mmCross section: 0.5 mm²; Length: 8 mm ... 9 mmCross section: 0.75 mm²; Length: 8 mm ... 9 mmCross section: 1 mm²; Length: 8 mm ... 9 mmCross section: 1.5 mm²; Len...**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / FK-MCP 1,5/ 6-ST-3,81 BD14-9SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.