

INDUSTRIAL COMPONENT DATA

MVSTBW 2,5/ 4-ST-5,08 GY H1L 1090785 PHOENIX CONTACT

Connector for printed circuit board, nominal current: 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBW 2,5/ 4-ST-5,08 GY H1L



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBW 2,5/ 4-ST-5,08 GY H1L
Catalog number	1090785
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-A8086E5384
Generated	2026-08-05

Product Overview

Connector for printed circuit board, nominal current: 12 A, number of poles: 4, pitch: 5,08 mm, type of connection:

Connection by screw with capsule-traction, color: grey, surface contacts: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MVSTBW 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: H1L Philipps-Recess with longitudinal groove, conductor connection direction/printed circuit board: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: packed in box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBW 2,5/ 4-ST-5,08 GY H1L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.