

INDUSTRIAL COMPONENT DATA

MVSTBW 2,5/ 6-ST-5,08 GY 1049287 PHOENIX CONTACT

Connector for printed circuit board, number of poles: 6, pi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBW 2,5/ 6-ST-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBW 2,5/ 6-ST-5,08 GY
Catalog number	1049287
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-19EC55121D
Generated	2026-08-06

Product Overview

Connector for printed circuit board, number of poles: 6, pitch: 5,08 mm, type of connection: Connection by screw with capsule-traction, color: grey, surface contacts: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: MVSTBW 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, conductor connection direction/printed circuit board: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed Conductive plate connector, nominal cross-section: 2.5 mm², colour: grey, nominal current: 12 A, reference voltage (III/2): 320 V, contact area: Sn, contact type: Female connector, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, item range: MVSTBW 2.5/.. -ST, pitch: 5.08 mm, connection type: Screwed connection with ring, screw driving surface: L Longitudinal slot, conductor/PCB plugging direction: -90 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2.5, locking: without, fastening type: without, packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical characteristicsProduct PropertiesProduct Type Conductive Plate Connector

Product range MVSTBW 2,5/.. -ST

Product Line COMBICON Connectors M

Number of poles 6

Steps 5.08 mm
Number of connections 6
Number of rows 1
Number of potentials 6
Data Management Status
Revision of the article 01
Electrical properties Rated Current IN 12 A
Rated voltage UN 320 V
Contact resistance 2.6 mΩ
Reference voltage (III/3) 250 V
Rated Shock Resistance Voltage (III/3) 4 kV
Rated Voltage (III/2) 320 V
Rated Shock Withstand Voltage (III/2) 4 kV
Reference voltage (II/2) 630 V
Rated Shock Withstand Voltage (II/2) 4 kV
Connection features Connection technology
Connector System COMBICON MSTB 2,5
Nominal cross-section 2.5 mm²
Contact Type Female connector
Locking
Lock Mode without
Mounting Flange without
Conductor connection
Connection type Screwed connection with ring
Conductor/PCB Plugging Direction -90 °
Rigid conductor cross-section 0.2 mm² ... 2.5 mm²
Soft conductor section 0.2 mm² ... 2.5 mm²
Conductive section. AWG 24 ... 12
Soft conductor section with end cap, without plastic bushing 0.25 mm² ... 2.5 mm²
Soft conductor section with plastic end cap and socket 0.25 mm² ... 2.5 mm²
2 rigid conductors of the same cross-section 0.2 mm² ... 1 mm²
2 flexible conductors of the same cross-section 0.2 mm² ... 1.5 mm²
2 conductors of the same cross-section, flexible with plastic sleeveless end cap 0.25 mm² ... 1 mm²
2 flexible conductors of the same cross-section with TWIN bit and plastic socket 0.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBW 2,5/ 6-ST-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.