

INDUSTRIAL COMPONENT DATA

PTN 2,5 3213963 PHOENIX CONTACT N disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTN 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTN 2,5
Catalog number	3213963
Category	Neutral disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-21FED7C1CB
Generated	2026-08-01

Product Overview

N disconnect terminal block

Sectionable neutral terminal, Note on assembly: To securely fix the neutral busbar, trestles must be placed at the beginning and end of each terminal strip, as well as longer strips every 20cm., nominal voltage: 250 V, nominal current: 24 A, Push-in connection, 1st floor, Dimensioning section: 2.5 mm², section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3213963

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 85 (C-1-2017)

GTIN 4046356609494

Weight per Piece (excluding packing) 8.440 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Note Assembly instructions:For secure fastening of the neutral busbar, supports must be set at the beginning and end of

each terminal strip as well as every 20 cm on longer terminal strips.

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 4 mm²

Color blue

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Maximum load current 24 A (with 4 mm² conductor cross section)

Nominal current I_N 24 A

Nominal voltage U_N 250 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.14 mm² / 0.2 kg

4 mm² / 0.9 kg

Tensile test....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTN 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.