

INDUSTRIAL COMPONENT DATA

NBC-FSDBP/0,15-93E/R4AC 1035210 PHOENIX CONTACT

Network cable NBC-FSDBP/0,15-93E/R4AC 1035210

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-FSDBP/0,15-93E/R4AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-FSDBP/0,15-93E/R4AC
Catalog number	1035210
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-B0D8115EAC
Generated	2026-08-04

Product Overview

Network cable - NBC-FSDBP/0,15-93E/R4AC - 1035210

Ready-made Ethernet cable, CAT5e, shielded, 2 pairs, flexible AWG 26 (7 wire), RAL 5021 (aqua blue), M12 built-in mount female, SPEEDCOM backwall mount/bolted mount to RJ45/IP20 male connector, Line, length 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Assembled Ethernet cable, CAT5e, shielded, 2-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), M12 flush-type socket, rear/screw mounting with SPEEDCON to RJ45 male connector/IP20, line, length 2 m

Key Commercial Data

Orderkey 1035210

Packing unit 1

GTIN 4055626540689

Custom tariff number 85444290

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

ETIM for 1035210 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

Other

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

0.15 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-20 °C

Rated current I_n (EF008250)

2 A

Rated voltage (EF000228)

48 V

Degree of protection (IP) (EF005474)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-FSDBP/0,15-93E/R4AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.