

## INDUSTRIAL COMPONENT DATA

# NBC-FSDBP/0,3-93E/R4AC-M04 1033367 PHOENIX CONTACT

## Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-FSDBP/0,3-93E/R4AC-M04



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                           |
| MPN / Reference | NBC-FSDBP/0,3-93E/R4AC-M04                |
| Catalog number  | 1033367                                   |
| Category        | Circular connector, mounting (with cable) |
| Minimum order   | 100 Pcs                                   |
| Document ID     | EO-7D157333D7                             |
| Generated       | 2026-08-05                                |

### Product Overview

Network cable

Network cable, cable length: 0.3 m, number of poles: 4, 100 MBit/s, CAT5, cable output: straight, Ethernet

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Field Device Connectors (FDC)

### Additional Product Information

Technical dataMountingMounting type Rear wall/screw mounting

Product propertiesProduct type Circular connectors (device side)

Type M12

Sensor type Ethernet

Number of positions 4

No. of cable outlets 1

Shielded yes

Coding D

Cable outlet straight

Data management status

Article revision 01

Material specificationsOuter sheath, material PUR

Conductor material Bare Cu litz wires

Electrical propertiesRated voltage (III/3) 72 V (DC)

Nominal voltage UN 48 V  
Nominal current IN 2 A  
Transmission medium Copper  
Transmission characteristics (category) CAT5 (IEC 11801:2002)  
Mechanical propertiesMechanical data  
Insertion/withdrawal cycles  $\geq 100$   
ConnectorConnection 1  
Type Flush-type female connector straight M12  
Locking type SPEEDCON  
Coding type D  
Shielded yes  
Degree of protection IP20  
Connection 2  
Type Plug straight RJ45  
Degree of protection IP20  
Cable/lineCable length 0.30 m  
Ethernet flexible CAT5, 2-pair [93E]  
Dimensional drawing  
Cable weight 42 kg/km  
UL AWM Style 20963 (80°C/30 V)  
Wiring standards/regulations Electrical requirements EN 50288-2-2  
Number of positions 4  
Shielded yes  
Cable type Ethernet flexible CAT5, 2-pair [93E]  
Conductor structure 2x2xAWG26/7, SF/UTP  
Signal runtime 5.3 ns/m  
Conductor structure signal line 7x 0.16 mm  
AWG signal line 26  
Conductor cross section 2x 2x 0.14 mm<sup>2</sup>  
Wire diameter incl. insulation 0.98 mm  
External cable diameter 6.40 mm  $\pm 0.2$  mm  
Outer sheath, material PUR  
External sheath, color water blue RAL 5021  
Conductor material Bare Cu litz wires  
Material wire in...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-FSDBP/0,3-93E/R4AC-M04 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.