

INDUSTRIAL COMPONENT DATA

NBC-M 8MS/ 1,5-93C/R4AC CH-MA 1157865 PHOENIX CONTACT Network cable, Ethernet (100 MBit/s), PROFINET (100 MB..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M 8MS/ 1,5-93C/R4AC CH-MA



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M 8MS/ 1,5-93C/R4AC CH-MA
Catalog number	1157865
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-0478C4D3CA
Generated	2026-08-05

Product Overview

Network cable, Ethernet (100 MBit/s), PROFINET (100 MBit/s), EtherCAT® (100 MBit/s), 4-pole, halogen-free PUR, green RAL 6018, shielded, M8 straight connector, coding: A / IP67, a RJ45 / IP20 straight connector, cable length: 1.5 m, Customer variant

Network cable, Ethernet (100 MBit/s), PROFINET (100 MBit/s), EtherCAT®(100 MBit/s), 4-pole, halogen-free PUR/FRNC, RAL 6018 green, shielded, M8/ IP67 straight connector, encoding: A, a RJ45 / IP20 straight connector, cable length: 1.5 m, Client variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1157865 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

Other

Type of plug-in contact, field sided (EF006269)

Male (plug)
Positioning cable feed, field-sided (EF005928)
Straight
Type of electrical connection, box-sided (EF005524)
M8
Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
1.5 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
Yes
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-40 °C
Rated current I_n (EF008250)
1 A
Rated voltage (EF000228)
30 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M 8MS/ 1,5-93C/R4AC CH-MA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.