

INDUSTRIAL COMPONENT DATA

NBC-M12FSD/ 2,0-93C/R4AC 1038740 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12FSD/ 2,0-93C/R4AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12FSD/ 2,0-93C/R4AC
Catalog number	1038740
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-BD47B50B79
Generated	2026-08-03

Product Overview

Network cable

Network cable, PROFINET CAT5 (100 MBit/s), EtherCAT® CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), RJ45 / IP20 straight connector, to M12 straight female, encoding: D / IP67, cable length: 2 m

Network cable, PROFINET CAT5 (100 MBit/s), EtherCAT® CAT5 (100 MBit/s), 4-pole, halogen-free PUR/FRNC, green RAL 6018, shielded (Advanced Shielding Technology), Straight female M12, coding: D / IP67, a Straight RJ45 / IP20 connector, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1038740

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626592749

Weight per Piece (excluding packing) 149.440 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 2 m

Ambient conditions

Degree of protection IP65 (M12 connector)

IP67 (M12 connector)

IP20 (RJ45 connector)

Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)

-25 °C ... 60 °C (RJ45 connector)

General data

Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling)

Further products with variable cable type and variable cable length can be found in the accessories section

Rated current at 40°C 1 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps

EtherCAT®CAT5 (IEC 11801), 100 Mbps

Standards/regulations M12 connector IEC 61076-2-101

Characteristics head 1

Head type Plug straight RJ45 / IP20

No. of positions (pin connector pattern) 4 (8)

Color black

Material (component) CuSn (Contact)

Ni/Au (Contact surface)

PA (Contact carriers)

PA (Housing)

Insertion/withdrawal cycles ≥ 750

Ambient temperature (operation) -25 °C ... 80 °C

Characteristics head 2

Head type Socket straight M12 / IP67

No. of positions (pin connector pattern) 4

Coding D (Data)

Color black

black

Material (component) CuSn (Contact)

Ni/Au (Contact su...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12FSD/ 2,0-93C/R4AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.