

INDUSTRIAL COMPONENT DATA

NBC-M12MR/ 2,0-94L/M12FR 1192098 PHOENIX CONTACT

Network Cable, CAT5e Ethernet (1 GBit/s), 8-pole, TPE, high..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MR/ 2,0-94L/M12FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MR/ 2,0-94L/M12FR
Catalog number	1192098
Category	Sensor-actuator patch cord
Minimum order	10 Pcs
Document ID	EO-44AC0BFF5C
Generated	2026-08-04

Product Overview

Network Cable, CAT5e Ethernet (1 GBit/s), 8-pole, TPE, highly flexible, turquoise, M12 angled connector, encoding: A/IP65, to M12 angled female, encoding: A/IP65, cable length: 2 m

Network cable, Ethernet CAT5e (1 GBit/s), 8-pole, TPE, turquoise, M12 / IP65 bent connector, encoding: A, to Female bent M12 / IP65, encoding: A, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1192098 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

8

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Female (bus)

Positioning cable feed, field-sided (EF005928)

Angled

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Angled

Cable length (EF000536)

2 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature during assembling/handling (EF001685)

-40 °C

Rated current I_n (EF008250)

2 A

Rated voltage (EF000228)

48 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MR/ 2,0-94L/M12FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.