

**INDUSTRIAL COMPONENT DATA**

# NBC-M12MS/15,0-94L/R4AC 1192092 PHOENIX CONTACT

## Network cable, CAT5e Ethernet (1 GBit/s), 8-pole, TPE, very ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MS/15,0-94L/R4AC



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | NBC-M12MS/15,0-94L/R4AC    |
| Catalog number  | 1192092                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 25 Pcs                     |
| Document ID     | EO-7EAF7F4BE8              |
| Generated       | 2026-08-05                 |

### Product Overview

Network cable, CAT5e Ethernet (1 GBit/s), 8-pole, TPE, very flexible, turquoise, M12 straight connector, coding: A / IP65, to RJ45 / IP20 straight connector, cable length: 15 m

Network cable, Ethernet CAT5e (1 GBit/s), 8-pole, TPE, turquoise, M12 / IP65 straight connector, encoding: A, a RJ45 / IP20 straight connector, cable length: 15 m

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

### Additional Product Information

ETIM for 1192092 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

8

Type of electrical connection, field-sided (EF005525)

Other

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

15 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature during assembling/handling (EF001685)

-40 °C

Rated current I<sub>n</sub> (EF008250)

2 A

Rated voltage (EF000228)

48 V

Degree of protection (IP) (EF005474)

IP65

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MS/15,0-94L/R4AC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.