

**INDUSTRIAL COMPONENT DATA**

# NBC-M12MS/ 2,0-94L 1192130 PHOENIX CONTACT Network cable, CAT5e Ethernet (1 GBit/s), 8-pole, TPE, very flexi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MS/ 2,0-94L



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | NBC-M12MS/ 2,0-94L         |
| Catalog number  | 1192130                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 10 Pcs                     |
| Document ID     | EO-E4D3AA0130              |
| Generated       | 2026-08-03                 |

## Product Overview

Network cable, CAT5e Ethernet (1 GBit/s), 8-pole, TPE, very flexible, turquoise, M12 straight connector, encoding: A/IP65, to free cable end, cable length: 2 m

Network cable, Ethernet CAT5e (1 GBit/s), 8-pole, TPE, turquoise, M12 / IP65 straight connector, encoding: A, to free cable end, cable length: 2 m

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

## Additional Product Information

ETIM for 1192130 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

8

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Male (plug)  
Positioning cable feed, box-sided (EF005927)  
Straight  
Cable length (EF000536)  
2 m  
Material of cable sheath (EF004136)  
Other  
Halogen free (EF000025)  
Yes  
Colour cable sheath (EF008249)  
Other  
With LED indication (EF005950)  
No  
Screened (EF000881)  
Yes  
Vulcanize (EF004115)  
No  
Material contact body (EF008248)  
Other  
Material of contact surface (EF004020)  
Other  
Permitted cable outer temperature during assembling/handling (EF001685)  
-40 °C  
Rated current I<sub>n</sub> (EF008250)  
2 A  
Rated voltage (EF000228)  
48 V  
Degree of protection (IP) (EF005474)  
IP65

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MS/ 2,0-94L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.