


INDUSTRIAL COMPONENT DATA

NBC-M12MSD/15,0-93C/M 8MS 3X4 1484396 PHOENIX CONTACT CAT5 network cable (100 MBit/s), 4-pole, halogen-free ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/15,0-93C/M 8MS 3X4



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/15,0-93C/M 8MS 3X4
Catalog number	1484396
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-C6B256E132
Generated	2026-08-05

Product Overview

CAT5 network cable (100 MBit/s), 4-pole, halogen-free PUR, green RAL 6018, Straight M12 connector, coding: D / IP67, a Straight M8 connector, coding: A / IP67, cable length: 15 m

CAT5 Network Cable (100 MBit/s), 4-pole, M12 Straight Connector, Coding: D/IP67, A M8 Straight Connector, Coding: A/IP67, Cable Length: 15m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataItem PropertiesProduct Type Ready-made data cable

Number of poles 4

application Standard

Number of Cable Outlets 1

Shielded Yes

Insulation Properties

Surge Category II

Degree of pollution 3

InterfacesBus system PROFINET

Electrical PropertiesNominal voltage UN 48 V AC

60 V DC
Nominal Current IN 4 A
Transmission Medium copper
Material DataFlammability class according to UL 94 V0
ConnectorsConnection 1
Construction M12 / IP67 Straight Connector
Encoding Type D (Data)
Grip body color black
Material CuSn (Contact)
Ni/Au (Surface Contacts)
TPU GF (Contact Support)
TPU, low flammable, self-extinguishing (Grip body)
Zinc die-casting, nickel-plated (Screw connection)
Plug Cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Tightening torque 0.2 Nm
Protection Index IP67
Ambient Temperature (Service) -25 °C ... 90 °C
Connection 2
Construction M8 / IP67 Straight Connector
Number of poles 4
Encoding Type to
Grip body color black
Material CuSn (Contact)
Ni/Au (Surface Contacts)
TPU GF (Contact Support)
TPU, low flammable, self-extinguishing (Grip body)
Zinc die-casting, nickel-plated (Screw connection)
Protection Index IP67
Cable/LineCable length 15 m
PROFINET CAT5 [93C] drag chain
Dimension Scheme
Shielded Yes
Cable Weight 61 kg/km
Cable type PROFINET CAT5 drag chain
Abbreviation 2YH(ST)C11Y
Cable Type (abbreviation) 93C
Signal Type/Category PROFINET CAT5 (IEC 11801), 100 MBit/s
EtherCAT@CAT5 (IEC 11801), 100 MBit/s
Cable Structure 1x4xAWG22/7, SF/TQ
Cable...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/15,0-93C/M 8MS 3X4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.