

INDUSTRIAL COMPONENT DATA

NBC-M12MSD/15,0-93X/M12MSD OD 1274312 PHOENIX CONTACT Network cable, PROFINET CAT5 (100 MBit/s), Ethernet CA..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/15,0-93X/M12MSD OD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/15,0-93X/M12MSD OD
Catalog number	1274312
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-9D5C863C3B
Generated	2026-08-04

Product Overview

Network cable, PROFINET CAT5 (100 MBit/s), Ethernet CAT5 (100 MBit/s), 4-pole, halogen-free PE-X, black RAL 9005, shielded, M12 straight connector, encoding: D / IP65, a M12 straight connector, encoding: D, cable length: 15 m, for outdoor applications, with stainless steel knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1274312 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)
M12
Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
15 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-50 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-40 °C
Rated current I_n (EF008250)
4 A
Rated voltage (EF000228)
48 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/15,0-93X/M12MSD OD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.