

INDUSTRIAL COMPONENT DATA

NBC-M12MSD/ 3,0-93E/R4AC VA 1093490 PHOENIX CONTACT

Network cable, Ethernet CAT5 (100 Mbps) CAT5, 4-position..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/ 3,0-93E/R4AC VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/ 3,0-93E/R4AC VA
Catalog number	1093490
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B59952A47C
Generated	2026-08-05

Product Overview

Network cable, Ethernet CAT5 (100 Mbps) CAT5, 4-position, shielded, Plug straight M12 / IP67, coding: D, on Plug straight RJ45 / IP20, cable length: 3 m

Network cable, CAT5 Ethernet (100 MBit/s) CAT5, 4-pole, shielded, M12 straight connector, encoding: D / IP67, to RJ45 / IP20 straight connector, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1093490

Packing unit 1

GTIN 4055626912196

Custom tariff number 85444290

Drawings

General data

Characteristics head 2

Cable

Dimensions

Characteristics head 1

Standards and Regulations

Classifications

Drawings

Dimensional drawing

Plug, M12 x 1, straight, shielded

Dimensional drawing

RJ45 connector, IP20

Circuit diagram

Contact assignment of the M12 and RJ45 plug

Schematic diagram

Pin assignment M12 male connector, 4-pos., D-coded, male side

Schematic diagram

Connector pin assignment plug RJ45

Cable cross section

PUR ETHERNET 2x2 FLEX [93E]

Back to topDimensions

Length of cable 3 m

Back to topGeneral data

Rated current at 40°C 1 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)

Rated voltage 48 V AC

60 V DC

Number of positions 4

Signal type/category Ethernet CAT5 (IEC 11801:2002), 100 Mbps

Standards/regulations M12 connector IEC 61076-2-101

Overvoltage category II

Degree of pollution 3

Alternative short product description Ethernet cable

Contact material CuSn

Contact carrier material PA 6.6

Contact surface material Ni/Au

Back to topCharacteristics head 1

Head type Plug straight M12 / IP67

No. of positions (pin connector pattern) 4

Coding D (Data)

Color black

Material (component) CuZn (Contact)

Ni/Au (Contact surface)

PA (Contact carriers)

TPU, hardly inflammable, self-extinguishing (Grip)

Zinc die-cast, nickel-plated (Screw connection)

Insulation resistance $\geq 100 \text{ M}\Omega$

Insertion/withdrawal cycles ≥ 100

Torque 0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/ 3,0-93E/R4AC VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.