

INDUSTRIAL COMPONENT DATA

NBC-M12MSX/5,04-94C 1630900 PHOENIX CONTACT Network cable, Ethernet CAT5 (1 GBit/s) CAT5 (1 GBit/s), 8-pole,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSX/5,04-94C



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSX/5,04-94C
Catalog number	1630900
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-50EEBCCAE2
Generated	2026-08-03

Product Overview

Network cable, Ethernet CAT5 (1 GBit/s) CAT5 (1 GBit/s), 8-pole, halogen-free PUR, water blue RAL 5021, Straight connector M12, encoding: X / IP67, a Straight connector M12, encoding: X / IP67

Network cable

Network cable, Ethernet CAT5 (1 Gbps) CAT5 (1 Gbps), 8-position, Plug straight M12, coding: X / IP67, on Plug straight M12, coding: X / IP67

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Sensor type Ethernet

Number of positions 8

No. of cable outlets 1

Coding X

InterfacesBus system Ethernet

Signal type/category Ethernet CAT5 (IEC 11801:2002), 1 Gbps

SignalingStatus display No

Status display present No

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

Nominal current IN 0.5 A
Transmission medium Copper
Transmission characteristics (category) CAT5 (IEC 11801:2002)
ConnectorConnection 1
Type Plug straight M12 / IP67
Number of positions 8
Coding type X (Data)
Handle color black
Material CuZn (Contact)
Ni/Au (Contact surface)
PP (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insertion/withdrawal cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Tightening torque 0.4 Nm
Degree of protection IP67
Ambient temperature (operation) -25 °C ... 90 °C
Connection 2
Type Plug straight M12 / IP67
Coding type X (Data)
Handle color black
Material CuZn (Contact)
Ni/Au (Contact surface)
PP (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insertion/withdrawal cycles ≥ 100
Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Tightening torque 0.4 Nm
Degree of protection IP67
Ambient temperature (operation) -25 °C ... 90 °C
Cable/lineEthernet drag chain CAT5, 4-pair [94C]
Dimensional drawing
Shielded yes
UL AWM Style 20963 (80°C/30 V)
Cable weight...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSX/5,04-94C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.