


INDUSTRIAL COMPONENT DATA

NBC-M12MR/ 5,0-94B US 1408751 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MR/ 5,0-94B SCO US



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MR/ 5,0-94B SCO US
Catalog number	1408751
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-65F4A147C7
Generated	2026-08-03

Product Overview

Network cable

Network cable, CAT5 Ethernet (1 GBit/s), 8-pole halogen-free, shielded, M12 angled connector, encoding: A/IP67, to free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1408751

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356827669

Weight per Piece (excluding packing) 250.000 g

Custom tariff number 85444210

Country of origin US (United States)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)

General data

Rated current at 40°C 2 A

Rated voltage 48 V AC

60 V DC

Number of positions 8

Signal type/category Ethernet CAT5 (on the basis of IEC 11801), 1 Gbps

Standards/regulations M12 connector IEC 61076-2-101

Contact material CuSn

Contact carrier material TPU GF

Contact surface material Ni/Au

Characteristics head 1

Head type Plug angled M12 SPEEDCON / IP67

Coding A (Standard)

Characteristics head 2

Head type free cable end

Color black

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Cable

Cable type Ethernet, flexible, CAT5

Cable type (abbreviation) 94B

UL AWM style 20963 (80°C/30 V)

Signal type/category Ethernet CAT5 (IEC 11801), 1 Gbps

Cable structure 4x2xAWG26/7; SF/UTP

Conductor cross section 4x 2x 0.14 mm²

AWG signal line 26

Conductor structure signal line 7x 0.16 mm

Core diameter including insulation 0.96 mm

Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown

Twisted pairs 2 cores to the pair

Overall twist 4 pairs for core

Shielding Aluminum-coated foil, tinned copper braided shield

Optica...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MR/ 5,0-94B SCO US with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.