

INDUSTRIAL COMPONENT DATA

NBC-MRD/ 2,0-93E SCO US 1406126 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MRD/ 2,0-93E SCO US



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MRD/ 2,0-93E SCO US
Catalog number	1406126
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-68A922F6D8
Generated	2026-08-04

Product Overview

Network cable

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole halogen-free, shielded, M12 angled connector, coding: D/IP67, to free cable end, cable length: 2 m

Network cable, Ethernet CAT5 (100 Mbps), 4-position, PUR halogen-free, water blue RAL 5021, shielded, Plug angled M12, coding: D / IP67, on free cable end, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Standard, U.S. cables

Sensor type Ethernet

Number of positions 4

Shielded yes

Coding D

InterfacesBus system Ethernet

Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps

SignalingStatus display no

Status display present No

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

Nominal current IN 4 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)

Transmission medium Copper

Transmission characteristics (category) CAT5 (IEC 11801:2002)

ConnectorConnection 1

Type Plug angled M12 / IP67

Coding type D (Data)

Material CuZn (Contact)

Ni/Au (Contact surface)

TPU GF (Contact carriers)

TPU, hardly inflammable, self-extinguishing (Grip body)

Zinc die-cast, nickel-plated (Screw connection)

Degree of protection IP67

Connection 2

Type free cable end

Cable/lineCable length 2 m

Ethernet flexible CAT5, 2-pair [93E]

Dimensional drawing

Cable weight 42 kg/km

UL AWM Style 20963 (80°C/30 V)

Wiring standards/regulations Electrical requirements EN 50288-2-2

Number of positions 4

Shielded yes

Cable type Ethernet flexible CAT5, 2-pair [93E]

Conductor structure 2x2xAWG26/7, SF/UTP

Signal runtime 5.3 ns/m

Conductor structure signal line 7x 0.16 mm

AWG signal line 26

Conductor cross section 2x 2x 0.14 mm²

Wire diameter incl. insulation 0.98 mm

External cable diameter 6.40 mm ±0.2 mm

Outer sheath, material PUR

External sheath, color water blue RAL 5021

Conductor material Bare Cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MRD/ 2,0-93E SCO US with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.