

INDUSTRIAL COMPONENT DATA

NBC-MS/ 5,0-93K/R4AQ SCO 1418875 PHOENIX CONTACT

Assembled Sercos III cable, shielded, star quad, 22 AWG str..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MS/ 5,0-93K/R4AQ SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MS/ 5,0-93K/R4AQ SCO
Catalog number	1418875
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-47103B6C8D
Generated	2026-08-05

Product Overview

Assembled Sercos III cable, shielded, star quad, 22 AWG stranded (7-wire), RAL 3020 (traffic red), M12 plug, SPEEDCON, 4-pos. to RJ45 plug/IP20, length: 7.5 m

Sercos III ready-made cable, shielded, star quads, flexible AWG 22 (7 wires), RAL 3020 (traffic red), M12 connector, SPEEDCON, 4 poles in RJ45/IP20 connector, length: 7.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Number of positions 4

No. of cable outlets 1

Shielded yes

Electrical propertiesNominal voltage UN 48 V AC

60 V DC

Transmission medium Copper

ConnectorConnection 1

Type Plug straight M12 SPEEDCON

Number of positions 4

Locking type SPEEDCON

Connection 2

Type Plug straight RJ45
Cable/lineCable length 5 m
Sercos III [93K]
Dimensional drawing
Cable weight 68 kg/km
UL AWM Style 21694 (60 °C / 600 V)
Number of positions 4
Shielded yes
Cable type Sercos III [93K]
Conductor structure 1x4xAWG22/7, SF/TQ
Signal runtime 5.3 ns/m
Conductor structure signal line 7x 0.25 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm²
Wire diameter incl. insulation approx. 1.55 mm
External cable diameter 6.50 mm ±0.2 mm
Outer sheath, material PVC
External sheath, color signal red RAL 3020
Conductor material Tin-plated Cu litz wires
Material wire insulation PE
Single wire, color white, yellow, blue, orange
Thickness, outer sheath approx. 0.90 mm
Type of pair shielding Aluminum-lined polyester foil
Overall twist Star quad
Max. conductor resistance ≤ 120 Ω/km
Insulation resistance ≥ 0.5 GΩ*km
Coupling resistance ≤ 20.00 mΩ/m (at 10 Hz)
Wave impedance 100 Ω ±15 Ω (at 100 MHz)
Nominal voltage, cable 600 V
Test voltage Core/Core 2000 V (50 Hz, 1 min.)
Test voltage Core/Shield 2000.00 V (50 Hz, 1 min.)
Minimum bending radius, fixed installation 3 x D
Minimum bending radius, flexible installation 7 x D
Smallest bending radius, fixed ins...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MS/ 5,0-93K/R4AQ SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.