

INDUSTRIAL COMPONENT DATA

NBC-M12MSD/25,0-93B/M12MSD 1047645 PHOENIX CONTACT Network Cable, PROFINET CAT5 (100 MBit/s), 4-pole, PUR/FR..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/25,0-93B/M12MSD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/25,0-93B/M12MSD
Catalog number	1047645
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-C02575E867
Generated	2026-08-04

Product Overview

Network Cable, PROFINET CAT5 (100 MBit/s), 4-pole, PUR/FRNC halogen-free, green RAL 6018, shielded, Plug straight M12 / IP67, coding: D, on Plug straight M12, cable length: 25 m

Network cable, PROFINET CAT5 (100 MBit/s), 4-pole, halogen-free PUR/FRNC, green RAL 6018, shielded, M12 / IP67 straight connector, coding: D, a M12 straight connector, cable length: 25 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1047645 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Male (plug)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

25 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-40 °C

Rated current I_n (EF008250)

4 A

Rated voltage (EF000228)

48 V

Degree of protection (IP) (EF005474)

IP67

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/25,0-93B/M12MSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.