

INDUSTRIAL COMPONENT DATA

NBC-MSD/25,2-939/MSD SCO SI 1425179 PHOENIX CONTACT

Network cable NBC-MSD/25,2-939/MSD SCO SI 1425179

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MSD/25,2-939/MSD SCO SI



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MSD/25,2-939/MSD SCO SI
Catalog number	1425179
Category	Patch cord copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-8216ACE755
Generated	2026-08-02

Product Overview

Network cable - NBC-MSD/25,2-939/MSD SCO SI - 1425179

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Network cable, PROFINET CAT5 (100 Mbps), 4-position, PE-X halogen-free, black, shielded, Plug straight M12 SPEEDCON / IP65, cable length: 25.2 m, Product tested according to customer specification/rail application

Key Commercial Data

Orderkey 1425179

Packing unit 1

GTIN 4055626386553

Custom tariff number 85444290

Dimensions

Length of cable 25.2 m

General data

Note The cable is 100% electrically tested for continuity.

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Overvoltage category II
Degree of pollution 3
Characteristics head 1
Head type Plug straight M12 SPEEDCON / IP65
No. of positions (pin connector pattern) 4
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Shielded yes
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 V0
Cable
Cable type PROFINET railway applications
Cable type (abbreviation) 939
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation 1.4 mm ±0.1 mm
Wire colors white-blue, orange-yellow
Overall twist Star quad
Shielding...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MSD/25,2-939/MSD SCO SI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.