

INDUSTRIAL COMPONENT DATA

NBC-M12MSD/ 3,5-93E/M12MSD 1421446 PHOENIX CONTACT

Network cable NBC-MSD/ 3,5-93E/MSD SCO 1421446

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/ 3,5-93E/M12MSD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/ 3,5-93E/M12MSD
Catalog number	1421446
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-B9C3E0A65E
Generated	2026-08-02

Product Overview

Network cable - NBC-MSD/ 3,5-93E/MSD SCO - 1421446

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, shielded, M12 straight connector, encoding: D SPEEDCON, a M12 straight connector, coding: D SPEEDCON, cable length: 3.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Network cable, Ethernet CAT5 (100 Mbps), 4-position, PUR, water blue RAL 5021, shielded, cable length: 3.5 m

Key Commercial Data

Orderkey 1421446

Packing unit 1

GTIN 4055626263274

Custom tariff number 85444290

Dimensions

Length of cable 3.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)

General data

Rated current at 40°C 4 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)

Rated voltage 48 V AC

60 V DC

Number of positions 4

Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps

Standards/regulations M12 connector IEC 61076-2-101

Contact material CuSn

Contact carrier material TPU GF

Contact surface material Ni/Au

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Cable

Cable type PUR ETHERNET 2x2 FLEX

Cable type (abbreviation) 93E

UL AWM style 20963 (80°C/30 V)

Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps

Cable structure 2x2xAWG26/7; SF/UTP

Conductor cross section 2x 2x 0.14 mm²

AWG signal line 26

Conductor structure signal line 7x 0.16 mm

Core diameter including insulation 0.98 mm

Wire colors white/orange-orange, white/green-green

Twisted pairs 2 cores to the pair

Overall twist Two pairs with two fillers to the core

Shielding Aluminum-coated foil, tinned copper braided shield

Optical shield covering 70 %

External sheath, color water blue RAL 5021

Outer sheath thickness 1.2 mm

External cable diameter D 6.4 mm ±0.2 mm

Minimum bending radi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/ 3,5-93E/M12MSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.